

# NEW! New Holland 35 hp Compact Tractor T1520



**LEAN & MEAN**  
JUST WHAT YOU NEED.



The NEW T1520 from New Holland gives you the best value for your hard-earned dollar, delivering reliable performance, rugged construction and easy operation.

#### **Reliable power**

The rugged 35-hp engine produces reliable horsepower and responds when you need extra power to pull you through tough conditions.

#### **Efficient operator deck**

The operating controls and instrumentation on the T1520 are convenient, straight-forward and refreshingly simple. The comfortable contoured seat glides on an inclined track to put you in the perfect operating position.

#### **A choice of transmission**

The 9x3 gear transmission gives you more speed choices than you'll find on other brand tractors. For

simple forward/ reverse changes and no-clutch convenience, choose the three-range hydrostatic transmission. You change speed and direction with a single foot pedal, making it easy to maneuver while mowing, loading or blowing snow.

#### **The T1520 is tough on work and easy on the wallet and includes these features:**

- The standard FWD axle provides added traction and better drawbar pull.
- Impressive 1,635-pound 3-point lift capacity to handle wider, heavier implements.
- Optional 7308 front loader makes it easy to move mulch, gravel, snow or hay.
- You can easily check engine oil or refuel without raising the hood.
- A wide selection of implements expands the versatility of the new T1520.

# T1520 Specifications

MODEL	T1520
<b>Engine</b>	
Gross engine hp (kW)	35 (26.1)
PTO hp (kW), gear transmission	29.5 (22.0)
PTO hp (kW), hydro. Transmission	28.0 (20.9)
Rated speed, rpm	2600
Cylinders	3
Aspiration	Natural
Displacement, cu.in. (L)	101.4 (1.7)
Fuel capacity, gal. (L)	7.1 (27)
<b>Transmissions</b>	
Gear	
Speeds forward/reverse	9 x 3
Min/Max forward speed with R4 tires, mph (k/hr)	0.71 - 12.1 (1.1 - 19.5)
Hydrostatic	
Ranges	3
Min/Max forward speed with R4 tires, mph (k/hr)	0 - 13.6 (0 - 21.9)
<b>Brakes</b>	
	Wet disc
<b>Power Take Off (PTO)</b>	
Rear PTO	
Gear transmission	Live 540 rpm
Hydrostatic transmission	Live 540 rpm
<b>Mid PTO</b>	
Gear transmission, optional	Live 2000 rpm
Hydrostatic transmission, standard equipment	Live 2000 rpm
<b>Hydraulics</b>	
Pump type	Gear
Pump capacity, gpm(Lpm)	6.2 (23.3)
Power steering pump, gpm(Lpm)	3.8 (14.2)
3-point hitch lift capacity, 24 in. aft of hitch, lb. (kg)	1635 (743)
<b>Dimensions</b>	
Overall length, with R4 tires, in. (mm.)	111.4 (2830)
Overall width (minimum) with R4 tires, in. (mm.)	62 (1575)
Wheelbase, in. (mm.)	63.0 (1600)
Height to top of ROPS, 4WD w/R4 tires, in. (mm.)	82.3 (2090)
Shipping weight, 4WD with R4 tires/9x3 trans., lbs. (kg)	2400 (1089)
<b>Tire Options</b>	
Bar R1 (Agricultural), front/rear	7.4 x 14      11.2 x 24
Turf R3, front/rear	24 x 8.50-14    13.6 x 16
Industrial R4, front/rear	25 x 8.50-14    15 x 19.5



#### Front Attachments

- Loader
- Quick-Attach Rotary Broom
- Quick-Attach Dozer Blade
- Quick-Attach Snow Blower

#### Mid Attachment

- Mid-Mount Mowers

#### Rear Attachments

- Finishing Mowers
- Flail Mowers
- Snow Blowers
- Utility Backhoes
- Rotary Tiller
- Post Hole Digger
- Ballast Box

Visit our Web site at [www.newholland.com/na](http://www.newholland.com/na) Or, call toll-free: **1-888-290-7377**



Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2007 CNH America LLC  
New Holland is a registered trademark of CNH America LLC.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

NH3160705 • 050750 • IPG • PRINTED IN U.S.A.