New Holland Automatic Bale Wagon

BW28 BW38 1037





Clear fields of bales fast

New Holland bale wagons pickup, haul and unload bales more efficiently than ever.

For over 40 years, New Holland bale wagons have transformed the back-breaking labor of moving and stacking bales into a job that's almost effortless. Now, New Holland makes this job faster and more comfortable than ever with the new BW Series self-propelled automatic bale wagons.

A new level of comfort and efficiency

The new BW Series cab is designed to keep you comfortable and efficient during even the longest days. The new swivel seat and redesigned side console and front instrument panel give you plenty of legroom and easier control. All machine functions are controlled with one, easy-to-use multifunction handle. The new curved windshield affords you a spectacular view. And the iso-mounted cab keeps things quiet reducing operator fatigue.

More power

Both the three-bale wide BW38 and the two-bale wide BW28 are powered by New Holland engines with increased horsepower compared to previous models. They also provide greater fuel economy and go easy on the environment with lower emissions.

Even more durability for years of service

These new models improve upon the New Holland legacy of reliability. New Holland engineers used state-ofthe-art Finite Element Analysis (FEA) to evaluate and eliminate the stress points in the main frame to ensure that these new bale wagons will serve many years of loading, hauling and stacking bales. The cab platform is now separated from the frame and mounted on isolators to protect it from twisting, vibration and noise. New, one-piece frame channels are made with thicker, 3/8-inch steel for added strength and durability.



Structural tubing is now used in place of formed channels for the cross members, adding strength and service life. And, the second table, load rack, rolling rack, and side supports have been redesigned for improved strength and durability.

A choice of models

New Holland offers one pull-type model and two new self-propelled

bale wagons to match your needs. The NEW BW28 easily loads 16 x18 two-tie bales and a variety of three-tie bales. The NEW BW38 is designed for three-bale-wide stacks of 14x18 or 16x18 bales. No matter which model you choose, you'll unload tightly packed, even stacks of bales without manual labor.

Model	Bale Size	Engine	Length	Width
BW28	15 x 22 or 15 x 23 16 x 22 or 16 x 23 16 x 18	New Holland 6.8 L 173 hp	30'11"	9'4"
BW38	14 x 18 or 16 x 18	New Holland 6.8 L 173 hp	30'11"	9'4"
1037	14 x 18 or 16 x 18	Pull-Type (requires 50 hp tractor)	25'6")	11'11"



Control and comfort

Redesigned cab makes you more efficient and comfortable.



Climb aboard a new self-propelled BW28 or BW38, and you'll find the redesigned cab holds little resemblance to previous models. New Holland has made sweeping improvements to assure your comfort and efficiency the moment you step inside.



This warning light display tower provides information on key functions.

Stretch out

Sit in the new swivel seat, and you have more legroom than ever before thanks to the redesigned tilt steering column and right-hand control console. You can adjust the air-ride seat and tilting steering wheel to fit you perfectly. Your comfort is enhanced further due to improved climate control. With double the number of vents, as well as a recirculation mode, you can control the flow of air conditioning and heat to suit your liking. Shading added to the top of the side windows helps keep you cool by cutting down on heat absorption.



Adjust the direction and flow from the overhead air conditioning and heater vents for maximum comfort.

Outstanding visibility

The new curved windshield and large side and rear windows provide excellent all-around visibility. And, the cab has been raised two inches for





All machine functions are conveniently located on one multi-function handle.

even better visibility, and reduced noise and vibration.

A 300% improvement in front lighting intensity increases your nighttime visibility so you can work as late as you need to. The new lighting package includes dual headlamps featuring high and low beams, as well as two additional work lights at the top of the cab. The cab is also pre-wired for an additional optional work light at the rear of the cab.

Improved control

The new multi-function handle makes operation easier than ever. You control all machine functions with one convenient handle. The handle position adjusts up and down, fore and aft and rotates to put it in the perfect position for you. The transmission shift lever and two-speed range selector switch are positioned conveniently to your right.

Little extras make a difference

The redesigned front instrument panel includes little additions that make a nice difference in your day, including the addition of cup holders and shelving, as well as a 12-volt power socket for a cell phone or other accessories. An inside rearview mirror provides second table visibility. And, there's space on the floor for a cooler.

The best way to pick up hay

Efficiency-boosting features make your job easier.

The new BW38 and BW28 selfpropelled bale wagons make loading and unloading bales as easy as driving. You control everything electronically from the cab.

Easy control of stack patterns

A new Stack Command[™] control system with a larger digital display is easy to read and use. It includes a stack counter function and allows you to program and control how you want the bales stacked on the table. Choose from an increased selection of pre-programmed stack patterns, as well as increased space for custom programs that you create. A "favorites" stack pattern function allows you to scroll through only those patterns you use the most making stack selection quicker and easier. As bales are added to the load, the digital readout lets you monitor bale loading.



The new Stack Command[™] control system provides up to 35 pre-programmed stack patterns as well as room for 20 custom patterns that you can program.

Optional flow control

If you deal with bales that vary greatly in weight, choose the new optional first table and/or auxiliary first table flow control valves. They allow you to adjust the delivery speed to match bale conditions.

Unload and go

When you're ready to unload, the multi-function handle lets you operate the load rack, rolling rack and push-off feet. The load rack has two raise speeds putting precise control at your fingertips. The rolling rack allows you to stack partial loads when necessary.

Five-speed versatility

A new five-speed automatic transmission with lock-up torque converter provides excellent speed matching ability. First gear provides a slower ground speed for increased productivity in high-density crops, while the overdrive in fifth gear provides for a fast 50 mph road speed.

Dual hydraulic systems

Two hydraulic systems with three pumps provide plenty of flow where it's needed. A 6.7 gpm (gallons per minute) gear pump provides flow for the power steering and brake booster. The bale loader and cross conveyor are supplied by a 13.8 gpm gear pump. And a 29.0 gpm piston pump provides flow for the closed-center system, which operates functions that require higher flow. Hydraulics now also drive the cooling fan for improved reliability and reduced maintenance. If fine dust and chaff are a big problem for you, the optional cooling fan reverser automatically reverses the fan after each load to help blow dirt out of the radiator and intercooler and chaff off the radiator screen.

Easier servicing

Two hydraulic valve manifolds one for the gear pumps and one for the piston pump—provide easier servicing. New four-piston rear disc brakes provide better braking performance and easier servicing than drum brakes. A sight gauge on the hydraulic tank takes only a glance to monitor the oil level.



After you select or create a stack pattern that fits your needs, the bales are configured automatically.



Labor saver

The 1037 lets you pick up and stack bales from the comfort of your tractor.

Put a New Holland 1037 pull-type bale wagon behind your tractor and you have a bale-stacking master that's ready for action. You can pick up, load and stack bales without moving from your tractor seat.

Four tons per load

The Model 1037 handles three-balewide loads and 14" x 18" or 16" x 18" bales—about four tons per load. Mechanically controlled tier formation makes a perfect stack every time. The rolling rack allows you to stack full or partial loads.

Simple controls

The Model 1037 is simple to use. Just hook up to your tractor's PTO, engage it and drive. The controls for bale pick up, loading and stacking are within easy reach. An optional remote control kit lets you put the controls right on your tractor. The open load-rack floor provides extra visibility when stacking.



The Model 1037 handles about four tons per load - 104 14"x 18" bales or 83 16"x 18" bales.





Specifications

Use the chart below to match your preferred bale size with the hauling capacity that you require.

		Pull-type 1037	Self-Prope		
Model Number	Model Number		BW38	BW28	
Average Tons Per Load		4	6	5	
-	Avg. Bale				
Bale Size	Weight, Alfalfa	Bales per load	Bales per load	Bales per load	
14 x 18 x 36	55-60 lbs.	104	161	*	
14 x 18 x 38	60-75 lbs.	104	161	*	
14 x 18 x 41	70-75 lbs.	104	161	*	
15 x 22 x 46	90-130 lbs.	*	*	84	
15 x 23 x 46	115-135 lbs.	*	*	84	
16 x 18 x 36	70-75 lbs.	83	161	*	
16 x 18 x 38	75-80 lbs.	83	161	*	
16 x 18 x 41	85-90 lbs.	83	161	*	
16 x 18 x 46	95-100 lbs.	*	*	107	
16 x 23 x 46	125-145 lbs.	*	*	74	
16 x 22 x 46	120-140 lbs.	*	*	74	
*= not applicable to this	s unit.				

Model Number	1037	BW38	BW28
Туре	Pull-type	Self-Propelled	Self-Propelled
Weight (empty), lbs. (kg)	5,410 (2454)	16,530 (7498)	16,040 (7230)
Length, ft (cm)	25'6" (777)	31'3" (853)	31'3" (853)
Width, minimum ft (cm)	*	9'11" (302)	9'4" (285)
Loader raised, max., ft (cm)	10'2" (310)	11'4" (345)	10'7" (322)
Loader lowered, ft (cm)	14'21.2" (433)	13'8" (417)	12'2" (371)
Height, ft (cm)	11'11" (363)	14'8" (477)	14'8" (477)
Wheel tread width, ft (cm)			
Front	*	80-1/8" (204)	80-1/8" (204)
Rear	6' (183)	69-1/2" (177)	69-1/2" (177)
Ground clearance, in (cm)	13" (33)	*	*
Front axle	*	9-5/8" (24)	9-5/8" (24)
Transmission	*	13-1/8" (33)	13-1/8" (33)
Wheelbase, ft (cm)	*	14'8" (447)	14'8" (447)
Overhead clearance (for stacking), ft (cm)			
16" x 18" bale	13' (396)	17'6" (533)	17'6" (533)
14" x 18" bale	14' (427)	16'10" (513)	17'6" (533)
15" x 22" bale	*	17'6" (533)	17'6" (533)
16" x 23" bale	*	*	17'6" (533)
Tires			
Front	*	39.5 x 15-19.5	39.5 x 15-19.5
Rear	11.00L x 15	40 x 19-19.5	40 x 19-19.5
Tractor power requirements, (min)	50 hp	*	*
Front disc brakes	*	15" (38)	15" (38)
Rear disc brakes	*	15-3/8" (39)	15-3/8" (39)
Engine	*	6.8L New Holland	6.8L New Holland
Horsepower, HP (kW)	*	173 (129)	173 (129)
Alternator	*	120 amp	120 amp
Fuel tank, gal (L)	*	75 (284)	75 (284)

Model Number	1037	BW38	BW28
Operating speeds, mph (kph)			
Loading	*	10 (16)	10 (16)
Hauling (on approved grounds)	*	30 (48)	30 (48)
Hydraulic pumps	10.5 gpm (39.7 Lpm)	Piston pump	Piston pump
Je on the he		29 gpm (110 Lpm)	29 gpm (110 Lpm)
		@ 2450 rpm (2050 psi)	@ 2450 rpm (2050 psi)
		Gear pump	Gear pump
		6.7 gpm (25 Lpm)	6.7 gpm (25 Lpm)
		@ 2450 rpm	@ 2450 rpm
		Gear pump	Gear pump
		13.8 gpm (52 Lpm)	13.8 gpm (52 Lpm)
		@ 2450 rpm	@ 2450 rpm
Hydraulic valves	Manual spool valve	Electro-hydraulic	Electro-hydraulic
		Two manifold valve	Two manifold valve
		assemblies	assemblies
Bale length, in (cm)			
Minimum	34 (86)	36 (91)	44 (118)
Maximum	42 (106)	41 (104)	48 (122)
Stack size, in (cm)			
16 x 18, height	7 tiers	162 (411)	162 (411)
16 x 18, width	3 bales	120 (305)	92 (234) *
14 x 18, height	7 tiers	162 (411)	*
14 x 18, width	3 bales	114 (290) *	
16 x 23, height	*	*	151 (384)
16 x 23, width	*	*	92 (234)
15 x 22, height	*	*	157 (399)
15 x 22, width	*		92 (234)
Automatic tie tier		Standard	Standard
Max. hillside angle	10°	^	^

Hillside hauling kit

- Tractor-mounted
- remote controls
- Tier counter

Heater

- Weight boxWiper kitRadio
- Fan reverserFirst table flow
- control valve
- First table flow control valve

Weight boxWiper kitRadio

Fan reverser

Heater

- Auxiliary table flow control valve
- 16 x 18 bale kit

* = not applicable to this unit.

Put the specialists at New Holland to work for you

New Holland dealer are specialists in helping you make the best choices for productivity and profitability. It starts with innovative New Holland equipment and continues with expert service and support programs that are built around your needs. From tractors to haytools to combines and

more, you won't find a more comprehensive range of equipment than the New Holland brand ... or a business partner with a broader range of expertise than your New Holland dealer. Committed to your success, your dealer will work hand-in-hand with you to determine which New Holland equipment is right for your operation.

To keep you moving forward, your New Holland dealer will assist you with competitive-rate finance, lease and insurance plans available through New Holland Credit — customer-tailored



plans designed to maximize

cash flow and preserve working capital. Talk to your dealer, too, about the purchasing convenience afforded by the New Holland Plan.

And, after the sale, turn to your dealer for factorytrained service and total parts support. Your New Holland dealer is ready to

0000 0000 0000 0000

10.111

tion a rest. IT

answer all your questions, help in any decisions, and resolve problems — in the field or at the dealership. You wouldn't expect anything less from a specialist who understands the way you work.

See your New Holland dealer today. And talk to the specialists.



YOUR NEW HOLLAND DEALER

Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377



Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas. Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

