

New Holland Trailing Wheel Rakes

HT152 HT154



NEW HOLLAND



Pick up high-volume hay, form fast-drying windrows

Offered in seven working widths from 17'5" (8-wheel) to 36' (20-wheel), New Holland HT152 standard and HT154 deluxe trailing wheel rakes offer important design features to help you move more hay and make bigger, fluffier windrows — fast. And for maximum durability, New Holland folding "Vee" wheel rakes are built to handle the rigors of high-speed operation in the toughest conditions.

Ask your New Holland dealer — your haymaking specialist — about New Holland wheel rakes, available in models designed

for both small and large-acreage producers.

- **Large surface area gets all the crop** — 55"-diameter raking wheels feature 40 tines each for gentle, but efficient hay pick-up and movement.
- **Extra durability built in** — thanks to the reinforced, articulating main frame.
- **Match wheel flotation to conditions** — individually adjust each raking wheel for optimum ground contact and flotation.
- **Easy transport over narrow roads** — all units feature 15" tires and fold down to 8'3" for transport. Hydraulic-fold

frame lets you change between transport and field positions from the comfort of your tractor seat.

- **No caster shimmy** — adjustable friction disc brake on the caster wheels steady the wheels in field operations and eliminate high-speed shimmy when transporting.
- **Change windrow width from your seat** — optional hydraulic kit lets you easily change windrow width between cuttings, even between fields, without leaving your tractor seat.

Specifications	HT152 Standard	
	8-wheel	10-wheel
Max. working width	17'5" (5.3 m)	20'4" (6.2 m)
Transport width	8'3" (2.5 m)	
Overall height	6'3" (1.9 m)	
Tire size	205-65 x 15"	
Number of raking wheels	8	10
Raking wheel diameter	55" (140 cm)	
Number of tines/wheels	40	
Max. field operating speed	14 mph (22.5 kph)	
Min. required tractor hp	30 (22 kW)	30 (22 kW)
Weight	2425 lbs (1100 kg)	2750 lbs (1247 kg)

Specifications	HT154 Deluxe				
	12-wheel	14-wheel	16-wheel	18-wheel	20-wheel
Max. working width	25' (7.6 m)	28'6" (8.7 m)	30'10" (9.4 m)	33'5" (10.2 m)	36' (11 m)
Transport width	8'3" (2.5 m)				
Overall height	6'3" (1.9 m)				
Tire size	205-75 x 15"				
Number of raking wheels	12	14	16	18	20
Raking wheel diameter	55" (140 cm)				
Number of tines/wheels	40				
Max. field operating speed	14 mph (22.5 kph)				
Min. required tractor hp	30 (22 kW)	40 (30 kW)	40 (30 kW)	55 (41kW)	55 (41kW)
Weight	3400 lbs (1542 kg)	4400 lbs (1996 kg)	4470 lbs (2028 kg)	5210 lbs (2363 kg)	5540 lbs (25132 kg)



New Holland wheel rakes produce big, fluffy windrows ... and they do it fast.



The HT152 standard and HT154 deluxe wheel rakes both fold down to a narrow 8' 3" for easy transport. The hydraulic-fold frame lets you change between transport and field positions right from your tractor seat.



Visit our Web site at www.newholland.com/na Or, call toll-free: **1-888-290-7377**

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.