

NEW! New Holland 55 to 60 hp Boomer™ Utility Tractors

T2410 T2420



At 55 and 60 horsepower, the new T2410 and T2420 are the biggest Boomer™ tractors New Holland has ever offered. Harness the power of one of these workhorses, and you can handle a long list of tough jobs fast.

Big Boomer™ power

Gutsy four-cylinder, 135.2-cu. in. displacement turbocharged engines deliver smooth response in the face of difficult conditions.

Choice of shuttle transmissions

The smooth-shuttling T2410 and T2420 are ideal for loader work, blade work and mowing. Choose a 12 x 12 Synchronized Shuttle Shift (SSS) transmission, or eliminate the need for clutching between forward and reverse with the deluxe 12 x 12 Electro-hydraulic Shuttle Shift (EHSS) transmission. The left-hand shuttle lever makes it easy to shuttle without removing your hand from the steering

wheel and frees your right hand to control the loader or implement.

Boomer™ comfort and visibility

The spacious Comfort Plus™ operator platform and sloped hood give you the easy operation and best-in-class visibility that have made Boomer tractors famous. A wide seat top with improved back and bolster support give you a ride that's even more comfortable.

Additional T2400 features include:

- The standard FWD axle provides added traction and better drawbar pull.
- Optional 270TL front loader makes it easy to move mulch, gravel, snow or hay.
- The one-piece, flip-up hood gives you complete access to all maintenance points.

T2410/T2420 Boomer™ Utility Tractors

MODEL	T2410	T2420
Engine		
Gross engine hp (kW)	55 (41.0)	60 (44.7)
PTO hp (kW)		
SSS transmission	47 (35.1)	51 (38.0)
EHSS transmission	46 (34.3)	50 (37.3)
Rated speed, rpm	2700	2800
Cylinders	4	4
Aspiration	Turbocharged	Turbocharged
Displacement, cu.in. (L)	135.2 (2.2)	135.2 (2.2)
Fuel capacity, gal. (L)	13.5 (51.1)	13.5 (51.1)
Transmissions		
12x12 Synchro Shuttle Shift (SSS)		
Min/Max forward speed with R4 tires, mph (k/hr)	1.1 to 17.5 (1.8 to 28.2)	1.1 to 18.1 (1.8 to 29.20)
12x12 Electro-Hydraulic Shuttle Shift (EHSS)		
Min/Max forward speed with R4 tires, mph (k/hr)	1.2 to 18.6 (1.9 to 30)	1.2 to 19.2 (1.9 to 31)
Brakes		
	Wet disc	Wet disc
Power Take Off (PTO)		
	Independent 540 rpm	Independent 540 rpm
Hydraulics		
Pump type	Gear	Gear
Pump capacity, gpm (lpm)*	11.6 (43.9)	12.0 (45.4)
Power steering pump, gpm (lpm)*	5.5 (20.8)	5.5 (20.8)
3-point hitch lift capacity, 24 in. behind the lift balls, lb. (kg)	3,465 (1571)	3,465 (1571)
* @ rated speed		
Dimensions (with R4 tires)		
Overall length with 3-point hitch, in. (mm)	137.3 (3487)	137.3 (3487)
Overall width (minimum), in. (mm)	71.6 (1819)	71.6 (1819)
Wheelbase, in. (mm)	74.8 (1900)	74.8 (1900)
Height to top of ROPS, in. (mm)	91.4 (2322)	91.4 (2322)
Shipping weight, lbs. (kg)	4260 (1932)	4260 (1932)
Tire Options		
Ag Tires		
Front	8 x 16 R1 9.5 x 16 R1	8 x 16 R1 9.5 x 16 R1
Rear	14.9-24 R1 OR 14.9-28 R1	14.9-24 R1 OR 14.9-28 R1
Turf Tires		
Front	27 x 10.5-15 R3	27 x 10.5-15 R3
Rear	44 x 18-20 R3	44 x 18-20 R3
Industrial Tires		
Front	12 x 16.5 R4	12 x 16.5 R4
Rear	18.4 x 24 R4	18.4 x 24 R4
Galaxy® Tires (not compatible with loader installation)		
Front	27/12LL x 15 R3	27/12LL x 15 R3
Rear	22.5LL x 16.1 R3	22.5LL x 16.1 R3

Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377



NEW HOLLAND

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2007 CNH America LLC
New Holland is a registered trademark of CNH America LLC.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

NH3160704 • 040725 • XXX • PRINTED IN U.S.A.