

New Holland 750 and 760 Series Heavy-duty Rotary Cutters

757GC 758GC 768GC 769GC



"Heavy duty" says it all about the performance and durability of New Holland 750 and 760 Series heavy-duty rotary cutters. Feature for feature, the new 750 and 760 Series are rugged, hard-working cutters that help you cover a lot of ground quickly, shredding thick weeds, stalks and brush with worry-free performance.

Four models, three cutting widths

Available in four models featuring 72", 84" and 96" cutting widths, 750 and 760 Series rotary cutters are built with heavier decks, heavy-duty gearboxes and outstanding cutting capacity for maintaining larger acreages. They're designed for use with utility, mid-range and high-horsepower tractors ranging from 40 to 150 maximum horsepower and with Category 1 or II hitches (depending on model).



Long-life and durability are built-in features

New Holland 750 and 760 Series heavy-duty rotary cutters put rugged performance to work for the long haul:

- 1/2" gearbox plate provides added durability
 - Heavy-duty A-frame and stump/debris jumper ensure long life
 - 1/2" x 4" heavy-duty high vacuum blades cut cleanly and smoothly
 - Bolt-on skid plates are counter-sunk – won't catch debris
 - Extra heavy-duty, four-plate slip clutch and flexible top link add protection
 - Chain guards are standard – evenly deflect clippings
 - 95 hp gearbox rating on 757GC and 758GC models; 125 hp gearbox on 768GC; 150 hp gearbox on 769GC.
- Includes a 5-year warranty (limited to defects in workmanship/material) on all models

New Holland 750 and 760 Series Rotary Cutter Specifications – Heavy-duty

MODEL:	757GC	758GC	768GC	769GC
	72"	84"	84"	96"
Tractor HP (max.)	95 HP	95 HP	140 HP	150 HP
Cutting Width	72"	84"	84"	84"
Overall Width	79"	90"	90"	102"
Overall Length	106"	122"	100"	97"
Hitch	3-point	3-point	3-point	3-point
Driveline Category	Cat. I	Cat. I	Cat. II	Cat. II
Gearbox Rating (HP)	95 HP	95 HP	140 HP	150/95 HP
Gearbox Warranty	5 Years	5 Years	5 Years	5 Years
Slip Protection	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch
Deck Gauge	7 Gauge	7 Gauge	7 Gauge	7 Gauge
Side Panel Depth	8" x 1/4"	8" x 1/4"	8" x 1/4"	8" x 1/4"
Blade Carrier	Pan	Pan	Pan	Pan
Output Shaft Diameter	2"	2"	2"	2"
Blade Size	1/2" x 4" Updraft	1/2" x 4" Updraft	1/2" x 4" Updraft	1/2" x 4" Updraft
Blade Tip Speed (540)	14,995 fpm	17,495 fpm	17,494 fpm	15,282 fpm
Cutting Height (min.)	2 inch	2 inch	2 inch	2 inch
Tail Wheel	Single Spindle	Single Spindle	Single Spindle	Dual Spindle
Tire & Wheel	Laminated	Laminated	Laminated	Laminated
Safety Deflectors	Rubber Belting	Front/Rear Chains	Front/Rear Chains	Front/Rear Chains
Weight (lbs)	1193	1504	1680	1749



YOUR NEW HOLLAND DEALER



Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2008 CNH America LLC
New Holland is a registered trademark of CNH America LLC.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

NH9250803 • 10830 • MG • PRINTED IN U.S.A.