

NEW! New Holland 900GH Series Utility Backhoes

920GH 930GH 940GH



New Holland is proud to introduce the 900 Series Utility Backhoes which incorporates a new curved design, new performance specifications, and significant improvements in operator visibility and operational comfort.

A new curved boom design creates increased visibility and also stays consistent with the Boomer™ tractor styling. A new grey seat matches the tractor's seat increasing operator comfort and productivity.

New Cast Iron Stabilizers and Stabilizing Pads are sturdy and strong to create increased support.

All models feature a common bucket which helps reduce dealer stocking levels.

All models feature two-lever control for easy operation of boom, dipper stick, bucket, and swing. Controls are mounted in a low-profile console for unobstructed vision.

New Holland 900GH Series Utility Backhoe Specifications

Model	756C (This model continues)	920GH	930GH	940GH
Tractor application	TC18-TC33/33DA/34DA TC30, TC1510, T1520, 1720, 1920	TC25/25D-TC55DA T2210 T2220, T2310, T2320, T2330, TC30, T1510, T1520, T2410, T2420	TC25D/25D-TC55DA T2210, T2220, T2310, T2320 T2330, TC30, T1510, T1520, T2410, T2420	TC48DA-TC55DA, T2410, T2420, TNA/TN, TLA/TL, TD Series 35 Series, 30 Series
Specifications				
Digging depth, in.	72	89.9	102	113.5
Reach from swing pivot, in.	107	123	134	149
Transport height, in.	68.5	79	84.7	96
Bucket rotation, degrees	171	180	180	180
Stabilizer spread-transport, in.	41	54	53	53
Stabilizer spread-operating, in.	78	79	91	91
Locking height, in.	57	—	—	—
Swing arc, degrees	180	180	180	180
Bucket digging forces, lbs.	2875	2875	4100	4100
Dipper stick digging forces, lbs.	1744	2020	2130	2670
Operating pressure, psi	2150	2150	2500	2500
Boom cylinder, in.	2.50 x 16.75	2.75 x 16.75	2.75 x 16.75	3.00 x 18.5
Dipper stick cylinder, in.	2.25 x 16.75	3.00 x 14.00	2.75 x 16.75	3.00 x 19.75
Bucket cylinder, in.	2.25 x 16.75	2.00 x 19.25	2.25 x 19.25	2.25 x 19.25
Swing cylinder, in.	2.25 x 6.85	2.25 x 8.97	2.25 x 8.97	2.25 x 8.97
Stabilizer cylinder, in.	2.25 x 10.25	2.25 x 10.66	2.25 x 14.00	2.25 x 14.00
Applicable buckets, in.	9, 12, 16	9, 12, 16, 18, 24, 36	12, 16, 18, 24, 36	12, 16, 18, 24, 36
Shipping weight, lbs.	785	875	980	1100

*Specifications vary with tractor model, hydraulic system, tire size, etc.



YOUR NEW HOLLAND DEALER



Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.