

New Holland Posthole Digger

906



NEW HOLLAND



Built for dependable drilling performance

Whether you're putting in a fence, constructing a pole barn or planting trees, you can rely on the durability of the 906 posthole digger. This digger drills precise-diameter holes quickly and easily. You control the depth and auger engagement right from your tractor seat using the tractor hydraulics and PTO.

Three models are available.

The light-duty model is for use with tractors up to 35 PTO hp; the medium-duty model matches up with tractors up to 55 PTO hp; and the heavy-duty model fits tractors up to 90 PTO hp. The light-duty model has a Category I

hitch, while the medium- and heavy-duty models have reversible hitch pins for use with Category I or II tractors. The drive shafts on all 906 posthole diggers are over-load protected.

Built to last.

Square tubular steel construction handles the torsional stress of a turning auger. Steel reinforcing provides extra support for the heavy-duty model. Machined, hardened-steel gears transfer power smoothly from tractor to auger. And, you get dependable service from these built-in features: hardened-steel input and output shafts that turn on tapered

roller bearings, universal joints with grease fittings, and a gearbox that runs in oil.

An assortment of augers.

Drill holes from six- to 24-inches in diameter and up to 42-inches deep. For extra-deep holes, an optional nine- or 14-inch auger extension increases the standard 42-inch digging depth to 51 or 56 inches. Most augers are available with double or semi-double flighting to match the job and soil conditions. All augers are equipped with replaceable cutting edges and auger points, so your posthole digger will perform like new even after years of use.

Specifications



An optional down pressure kit for the heavy-duty model provides extra digging force for drilling in hard and heavy soil.



Optional parking stand allows for easy hookup and storage.



Optional nine-inch or fourteen-inch (pictured) auger extensions increase digging depth.

Model	Light-Duty	Medium-Duty	Heavy-Duty
Hitch	Cat I	Cat I or II	Cat I or II
Input RPM on PTO	540.....
Maximum recommended tractor PTO horsepower	35	55	90
Drive protection	Shear Bolt.....
Output shaft diameter, in (cm)	2 (5).....
Drive shaft size (ASAE)	Cat I	Cat III	Cat IV
Square steel tube diameter	3.5 (8.9).....
Boom, in (cm)	3 (7.6).....
Mast, in (cm)
Down pressure kit	NA	NA	Optional
Weight, less auger, lbs (kg)	235 (106.6)	260 (117.9)	335 (151.9)
Augers			
Semi-double flight, in (cm)	6, 9 (15, 23)	6, 9, 12 (15, 23, 30)	6, 9, 12 (15, 23, 30)
Double flight, in (cm)	9 (23)	9, 12, 14, 18 (23, 30, 36, 46)	9, 12, 14, 18, 24 (23, 30, 36, 46, 61)
Cutting edge/Drill point	Replaceable.....
Maximum drilling depth, in (cm)	42 (107).....
Without extension	51 (130).....
With 9" extension	56 (142).....
With 14" extension

YOUR NEW HOLLAND DEALER



Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

Visit our website at www.newholland.com/na
Or, call toll-free at 1-888-290-7377

© 2001 New Holland North America, Inc.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.