

New Holland Mid-Mount Finishing Mower 914A



NEW HOLLAND



Cut mowing jobs down to size

The 914A mower turns your compact tractor into a highly maneuverable mowing machine. Since the 914A is mid-mounted under your tractor, it's easy to mow right next to trees, shrubs and buildings—and keep an eye on the job you're doing.

Efficient, even cutting. The 914A side-discharge is available in 54", 60" or 72" widths. The rear-discharge mower is available in 60", 72" or 84" widths. Three overlapping, high-lift blades provide efficient cutting action and a tip speed of up to 16,000 feet per minute. On the 84" mower—the widest mid-mount deck available—four GATOR MULCHER™ blades do the work while delivering a best-in-class blade overlap of 1½". The four-tooth blade design provides outstanding mulching and cut quality, especially in bahia grass. Side-discharge

mowers distribute clippings evenly through a large, right-side opening. Rear discharge/mulching mowers distribute mulched material evenly to the rear.

A four-bar parallel linkage allows the mower to move up and down, providing a close, even cut without scalping.

When fully raised, the 914A provides plenty of ground clearance to help prevent damage when operating in adverse conditions. You can raise and lower the deck with the tractor hydraulics. And, the mower deck can be locked in the raised position during transport, or when you're using the tractor for 3-point hitch jobs.

The 914A is compatible with New Holland front loaders, too. There's no need to remove the mower when you're ready to do loader work — both can be mounted on the tractor at the same time.

Easy height adjustment. Cutting height is easily adjusted, without tools, in half-inch increments from one-and-a-half to four inches to suit your needs.

Rugged construction and easy maintenance. The 914A mower features fabricated construction, built to stand up to the demands of continuous mowing. Shaft drive transfers power smoothly from tractor to mower.

Routine maintenance is easy. Spindles can be greased from the top of the mower deck without removing shields. You can apply grease to lubricating points on the wheel axles, caster spindles and U-joints to minimize wear.

The 914A is compatible with SuperSteer™ FWD.

Specifications

	Side-Discharge			Rear-Discharge		
Cutting width, in (cm)	54 (137.1)	60 (152)	72 (183)	60 (152)	72 (183)	84 (213)
Overall width, in (cm)	67 (170)	72.8 (185)	91.5 (232.4)	62.4 (158.5)	74.4 (189)	86.5 (220.3)
Cutting height, (estimated), in (cm)	1.3-4 (3.3-10.2)	1.5-4 (3.8-10.2)	1.5-4 (3.8-10.2)	1.5-4 (3.8-10.2)	1.5-4 (3.8-10.2)	2-4 (5.0-10.2)
Transport height, in (cm)	2.5 (6.4)	2.5 (6.4)	2.5 (6.4)	2.5 (6.4)	2.5 (6.4)	6 (15.2)
Deck gauge	7	7	7	7	7	7
Gauge wheels, in (cm)	6x2.5 (15.2x6.4)	6x2.5 (15.2x6.4)	6x2.5 (15.2x6.4)	6x2.5 (15.2x6.4)	6x2.5 (15.2x6.4)	6x2.5 (15.2x6.4)
Drive	shaft	shaft	shaft	shaft	shaft	shaft
PTO drive	Mid PTO	Mid PTO	Mid PTO	Mid PTO	Mid PTO	Mid PTO
Number of blades	3	3	3	3	3	4
Blade length, in (cm)	18.25 (46.4)	20.5 (52.1)	24.5 (62.2)	20.4 (51.8)	24.5 (62.2)	23 (58.6)
Blade width, in (cm)	2.5 (6.4)	2.5 (6.4)	2.75 (7.0)	2.5 (6.4)	3.0 (7.6)	3.0 (7.3)
Blade tip speed, fpm (mpm)	16,000 (4,876)	16,000 (4,876)	16,000 (4,876)	16,000 (4,876)	16,000 (4,876)	15,446 (4707)
Blade overlap, in (cm)	1 (2.5)	1.1 (2.9)	1 (2.5)	1.1 (2.9)	1 (2.5)	1.5 (3.8)
Approx. Weight, lb (kg)	440 (199.6)	475 (215.5)	525 (238.1)	424 (192.3)	520 (235.9)	775 (351.25)
Compatible with NH front-end loader models	7106	7106/7308	7308	7106/7308	7308	
Recommended Tractors	18.5 hp TC18 21 hp TC21/21D	18.5 hp TC18 21 hp TC21/21D 25 hp TC25/25D 29 hp TC29/29D 33 hp TC33/33D	29 hp TC29/29D 33 hp TC33/33D	18.5 hp TC18 21 hp TC21/21D	29 hp TC29/29D 33 hp TC33/33D	35 hp TC35D 40 hp TC40D

Front and rear gauge wheels adjust to six cutting heights

Seven-gauge stamped steel construction

Three overlapping blades

Side discharge mowers distribute clippings evenly through a large, right-side opening; rear discharge /mulching mowers distribute mulched material evenly to the rear

Front and rear gauge wheels adjust to six cutting heights

YOUR NEW HOLLAND DEALER



Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

Visit our website at www.newholland.com/na
Or, call toll-free at 1-888-290-7377

© 2001 New Holland North America, Inc.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

31091418 • 50115 • API • PRINTED IN U.S.A.