

# New Holland Front Blade

702C



NEW HOLLAND



## Front blade provides easy control, working comfort

If your neck gets sore watching rear implements work, it's time to get a 702C front blade for your compact diesel tractor. The 702C gives you pushing power up front for handling sand, manure, gravel or snow. And with your work out front, it's easier to see and maneuver.

**Single-lever, hydraulic control provides simple control of blade height.** Add the hydraulic angling function and you can control all blade functions with

one hand—from the driver's seat. Standard mechanical angling adjusts with a pin and provides two settings, left or right, up to 30 degrees.

Spring-trip design lets the blade pivot when it hits an obstruction, avoiding damage to the blade or tractor. Hydraulic float lets the blade follow ground contour—removing loose dirt, gravel, or snow while maintaining the previous shape of the land.

Adjustable skid shoes help prevent

gouging by maintaining the blade at a preset height. The shoes can be easily adjusted.

**The 702C can be quickly attached or removed with minimum effort.** The mounting bracket hugs the midsection of the tractor to maintain good ground clearance while protecting valuable tractor components.

The 702C is available in five-, six-and-one-half and seven-foot widths.



Single-lever control lets you operate the blade with one hand.



Blade lift is controlled hydraulically with this cylinder on the model 702C.

### 702C Front Blade Specifications

Recommended Tractors	<b>TC18/TC21/TC21D</b>	<b>TC25/TC25D/TC29/TC29D TC33/TC33D</b>	<b>TC35/TC35D/TC40/TC40D TC45/TC45D</b>
Moldboard width, in (cm)	60 (152.4)	78 (198.1)	84 (213.4)
Moldboard height, in (cm)	18 (45.7)	20 (50.8)	20 (50.8)
Moldboard thickness, in (cm)	.18 (.46)	.25 (.6)	.25 (.6)
Cutting edge, in (cm)	.....	.50 X 36 (1.2 X 15.2) Rvrs.....	.....
Blade lift height, * in (cm)	12 (30.5)	10 (25.4)	10.38 (26.4)
Digging Depth, * in (cm)	3 (7.6)	4.25 (10.8)	3 (7.6)
Adjustable skid shoes	standard	standard	standard
Max. blade angle	30°	30°	30°
Weight, lb (kg) (less hyd. angling)	389 (176.4)	587 (266.3)	660 (299.4)

\* Specifications may vary with the tractor model, tire size, lift cylinder mounting and whether tractor is equipped with two- or four-wheel drive.

## YOUR NEW HOLLAND DEALER



Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.  
 Visit our website at [www.newholland.com/na](http://www.newholland.com/na)  
 Or, call toll-free at 1-888-290-7377  
 © 2001 New Holland North America, Inc.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.