

# IMPLEMENTS - Front Two-Stage Snow Blower

*for 2WD and Conventional FWD Compact Tractors and Commercial Mowers*

MODEL	CUTTING WIDTH	ATTACHES TO
50CS	50"	TZ18DA, TZ24DA
716D	51"	TC18, TC21D, TC21DA, TC24D, TC24DA, TC30
716D	52"	MC22, MC28, MC35
62MS	62"	MC22, MC28, MC35
716D	63"	TC21D, TC21DA, TC24D, TC24DA, TC30
63CSH	63"	TC29, TC29D, TC29DA, TC33, TC33D, TC33DA
72CSH	72"	TC35D, TC35DA, TC40D, TC40DA, TC45DA

## Selling Points

**Two-stage design** allows you to throw and clear many types of snow, from light and fluffy to wet or hard-packed. Cutting height up to 26 inches.

**Auger has an open design** to prevent wet snow from building up and helps break up hard-packed snow.

**Blower fan** uses three or four blades.



**Heavy-duty, adjustable skid shoes** allow you to vary settings for efficient operation in changing conditions.

**Standard manual chute rotation** allows you to adjust the spout easily.

**Optional hydraulic chute rotator** allows you to change direction of blown snow without leaving the operator's seat.

**Optional hydraulic chute deflector** varies the discharge height from the operator's seat.

**Cutting edges** are replaceable and reversible for long life and easy maintenance.

**Shearbolt protection** is standard equipment.

**Quick-Attach hitch system** allows you to quickly change attachments without tools. You don't need separate frames to mount different attachments.



**NEW HOLLAND**

**Your success — Our specialty**

# IMPLEMENTS - Front Blades

*for 2WD and Conventional FWD Compact Tractors and Commercial Mowers*

MODEL	BLADE WIDTH	ATTACHES TO
54CB	54"	TZ18DA, TZ24DA
60CB	60"	TZ18DA, TZ24DA
702D	60"	TC18, TC21D, TC21DA, TC24D, TC24DA, TC30 MC22, MC28, MC35
702D	84"	TC48DA, TC55DA
72CB	72"	TC29, TC29D, TC29DA, TC33, TC33D, TC33DA
72CBH	72"	TC35D, TC35DA, TC40D, TC40DA, TC45DA
84CBH	84"	TC35D, TC35DA, TC40D, TC40DA, TC45DA

## Selling Points

**54", 60", 72" and 84" blade widths** handle snow, gravel or dirt with ease.

**Durable, heat-treated, high-carbon, replaceable and reversible cutting edge** bolts onto blade for long life and easy maintenance.



**One-lever hydraulic control** is easy to reach and allows you to raise and lower the blade and adjust blade angle.

**60", 72" and 84" blades can be hydraulically angled up to 30 degrees** to deliver material to the right or the left.

**Adjustable skid shoes** maintain blade at a preset height to prevent gouging.

**Durable, compact, spring-trip design** allows blade to pivot when it hits any obstruction.

**Quick-Attach hitch system** allows you to quickly change attachments without tools. You don't need separate frames to mount different attachments (excludes blade for TC48DA and TC55DA).



**NEW HOLLAND**

**Your success — Our specialty**

# IMPLEMENTS - Rotary Brooms

*for 2WD and Conventional FWD Compact Tractors and Commercial Mowers*

MODEL	CLEARING WIDTH	ATTACHES TO
47CO	47"	TZ18DA, TZ24DA
704D	60"	TC18 – TC24DA, TC29 – TC33DA, TC30, TC35D, TC35DA, TC40D, TC40DA, TC45DA MC22, MC28, MC35
72CO	72"	TC29 – TC33DA, TC30, TC35D, TC35DA, TC40D, TC40DA, TC45DA

## Selling Points

**60 and 70-inch broom head** sweeps leaves, clippings and snow using 22-inch, spacerless and convoluted brushes with polypropylene bristles.



**Broom can be manually angled** from 0 to 25 degrees.

**Optional hydraulic angling** available for 60" and 72" broom heads.

**The brush head pivots** if an obstacle is encountered to prevent damage.

**Parking stands** make mounting easy and protects the bristles when storing.

**Replacement brush heads** are available in polypropylene and polypropylene/wire construction.

**Quick-Attach hitch system** allows you to quickly change attachments without tools. You don't need separate frames to mount different attachments.



**NEW HOLLAND**

**Your success – Our specialty**

# LOADERS - Model 18LA

## Loaders for TC48DA and TC55DA Utility tractors

18LA LIFT CAPACITIES	TC48DA	TC55DA
at full height @ bucket pivot	2,500 lbs.	2,500 lbs.
at full height @ 19.7 in (500 mm) forward	1,830 lbs.	1,830 lbs.
to 59 inches @ bucket pivot	3,500 lbs.	3,500 lbs.
to 59 inches @ 19.7 in (500 mm) forward	2,213 lbs.	2,213 lbs.
BREAKOUT FORCE		
@ bucket pivot	5,000 lbs.	5,000 lbs.
@19.7 in (500 mm) forward	3,114 lbs.	3,114 lbs.
MAXIMUM LIFT HEIGHT		
	112.3 in	112.3 in.

## Selling Points

**3,500-pound lift capacity** at 59 inches, customers can easily lift pallets onto flat bed trucks.

**Quick-attach face plate and quick-attach bucket** saves time.

**The longer curved boom design** provides excellent reach and maximum lifting capabilities. It also provides greater strength with less weight and mass than conventional "dog-leg" booms used by competition.

**Skid-steer compatible** quick-attach face plate with quick-attach buckets, farm forks, bale spear are available.

**Best-in-class visibility.** No "dog leg" to obstruct your view to the front and sides. These loaders are specifically designed to complement Boomer™'s sloped hood design.

**Four-bar linkage** provides greater dump and roll back angles for better filling and dumping.

**Mid-mount design** means no front frame to interfere with tractor serviceability.



**Loader control valve** is nestled into the right fender for convenient control location.

**Order compact tractors "loader-ready" from the factory** to make it faster and easier to install loaders prior to delivery to customers.



**NEW HOLLAND**

Your success — Our specialty

# LOADERS - Model 10LA

## Loaders for TZ18DA and TZ24DA Sub-Compact tractors

LOADER	LIFT HEIGHT	LIFT CAPACITY	TRACTOR REQUIREMENTS
10LA	71.3 "	657 @ bucket pivot	TZ18DA or TZ24DA

## Selling Points

**Industry-leading curved boom design** provides best-in-class reach, better visibility, and greater strength with less weight and mass than conventional "dog-leg" loader booms. Operators can see easily to the top edge of the bucket from the tractor seat.

**Loader control valve** is conveniently located on the right loader mount with the lever just to the right of the steering wheel.



**Mid-mount frame design and quick-attach system** makes connecting and disconnecting the loader fast and simple. No tools are needed. The mid-mount design also makes it easy to service the tractor engine, radiator, battery and components that are under the hood.

**A bucket level indicator** is located inside the right boom arm to make it easy for operators to return to the pile with a level bucket.

**Four-bar linkage** provides greater rollback for more complete bucket filling and better material retention at travel height. It also provides a greater dump angle for cleaner dumping of sticky material.

**Industrial style cast reinforcements** offer greater strength and longer life.

**Rectangular torque tube** adds strength to resist boom twisting if there's a heavy load on one side of the bucket.



**NEW HOLLAND**

Your success — Our specialty

# IMPLEMENTS - Models 54CMS and 60CMS

## Mid-Mount Mowers for TZ18DA and TZ24DA Sub-Compact tractors

MODEL	SIZE	TRACTOR COMPATIBILITY
54CMS	54"	TZ18DA, TZ24DA
60CMS	60"	TZ18DA, TZ24DA

### Selling Points

**Quick-attach design** allows these mower decks to be attached and detached in minutes without tools.

**Two cutting widths** available—54 inches and 60 inches. Both discharge grass clippings to the side.



**Variable height adjustment** from one to five inches. Simply move the lever to your desired cutting height and lower the deck.

**Stamped steel construction** stands up to many seasons of use.

**Blade tip speed (fpm) spin** at up to 15,500 ft. per minute for smooth, efficient cutting action.

**Free-floating, four-bar linkage** allows the mower to move up and down to follow ground contours.



*Compatible with the 10LA front-end loader for greater versatility.*



**NEW HOLLAND**

**Your success — Our specialty**