

New Holland Rear-Mount Finishing Mower

930B



NEW HOLLAND



Make short work of big mowing jobs

The 930B rear-mounted finishing mower cuts big mowing jobs down to size. The 930B is available in four-, five-, or six-foot widths, and will fit most tractors under 40 PTO horsepower equipped with a Category I 3-point hitch and 540-rpm PTO. It's the perfect match for all compact diesels. And, since the 930B attaches and detaches easily, you can quickly free your tractor for other chores.

Air tunnel design for efficient cutting. You get efficient cutting action and even material discharge from the air tunnel design. Overlapping high-lift blades provide fast, thorough cutting. Clippings are distributed evenly

to the right side through a flip-up discharge chute.

Four gauge wheels permit even cutting and simple height adjustment. Four gauge wheels on the 60- and 72-inch models (three standard on the 48-inch model, fourth optional) permit the mower to closely follow the ground contour for an even cut without scalping. A floating top link offers additional flex that helps the 930B follow the ground through dips and over humps. You can adjust cutting height by placing spacers above or below the gauge wheel mounting bracket. Height can be adjusted in half-inch increments from one inch to

five-and-a-half inches to suit your needs, without tools.

Rugged construction and easy maintenance. A strong 40-hp gearbox teams up with a 540-rpm PTO to handle the stress of continuous mowing. Shaft drive transfers power smoothly from tractor to gearbox. And, the belt-driven spindles ride on tapered roller bearings for smooth operation and long life. A spring-loaded idler maintains proper blade drive belt tension. Maintenance is easy. Greasable spindles ensure trouble-free performance.

Put a 930B finishing mower to work for you. It will make short work out of big mowing jobs.

Specifications



Three gauge wheels on the 48-inch model and four gauge wheels on the 60- and 72-inch models allow you to adjust cutting height without tools.



Clippings are distributed evenly through the right-side discharge with spring-loaded shield.



Floating lift arms provide "flex" that helps the mower follow ground contours.

RECOMMENDED TRACTORS	4-FT. WIDTH	5-FT. WIDTH	6-FT. WIDTH
	TC18	TC21/21D	TC29D
	TC21/21D	TC24D	TC33D
	TC24D	TC29D	TC35/35D
		TC33D	TC40/40D
			TC45/45D

Cutting width, in (cm)	48 (122)	60 (152)	72 (183)
Deck design and constructionAir tunnel, fabricated.....		
Drive typeshaft and gearbox.....		
Drive methodrear 540-rpm PTO.....		
Gearbox rating, hp (kW)40 (53.6).....		
Blade driveV-belt.....		
Number of blades	2	3	3
Cutting height (est.), in (cm)1-5.5 (2.5-14.0).....		
Blade length, in (cm)	24.3 (61.7)	20.6 (52.3)	24.3 (61.7)
Blade width, in (cm)3 (7.6).....		
Blade tip speed, fpm (mpm)13930 (4246).....		
Blade overlap, in (cm)1 (2.5).....		
Number of spindles	2	3	3
Spindle diameter, in (cm)1 (2.5).....		
Spindle housingcast iron.....		
Spindle lubricationtop greasable.....		
Pulley materialcast iron.....		
Dischargeright-side.....		
Gauge wheels	3 pneumatic or 3 foam-filled with 4th optional	4 pneumatic or 4 foam-filled	4 pneumatic or 4 foam-filled
HitchCat. 1 3-pt.....		
Approx. weight, lb (kg)	482 (218.6)	584 (264.9)	618 (280.3)

YOUR NEW HOLLAND DEALER

Visit our Web site at www.newholland.com/na Or, call toll-free: **1-888-290-7377**

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2003 New Holland North America, Inc. New Holland and New Holland Credit are registered trademarks of New Holland North America, Inc.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

NH4240306 • 050303 • API • PRINTED IN U.S.A.

