

NEW! New Holland Zero-Turn-Radius Mowers

G4010 G4020 G4030 MZ19H



Designed with the homeowner in mind, the NEW G-Series mowers reduce mowing time compared to traditional lawn tractors, without sacrificing quality of cut. And, of course, G-Series mowers provide the ultimate in smooth maneuvering with zero-degree turning performance.

A quality cut

Available in 42- or 50-inch cutting widths, G-Series mower decks deliver premium cutting quality using a top-discharge design and high-lift blades that promote fast, even dispersal of clippings without clumps. Mower decks are a full four inches in depth, creating a vacuum action that allows the blades to cut clippings into fine particles.

Exceptional comfort

Two padded steering levers use hydraulic damping action to deliver smooth steering control without jerky movements and arm fatigue. The contoured, high-back seat with optional armrests (standard on G4030) provides an excellent vantage point that is comfortable too.

Built to last

Rugged G-Series construction includes a heavy-duty steel frame, a tubular steel axle and a cast-iron rear bumper. Bolts and nuts are used instead of the typical self tapping screws for added durability.

More high-performance G-Series features:

- NEW 3-year limited warranty.
- Premium Kohler engines deliver 19 to 23 horsepower.
- 7-mph ground speed lets you get every mowing job done fast.
- A deck washout port is provided for fast deck cleaning.
- A convenient foot pedal allows you to adjust cutting height on the go. (Standard on G4030, optional on other models)

Zero-Turn-Radius Mower Specifications

MODEL	G4010	G4020	G4030	MZ19H
Engine				
Horsepower, hp (kW)	19 (14.2)	21 (15.7)	23 (17.2)	19 (14.2)
Make	Kohler Courage SV590	Kohler Courage SV610	Kohler Courage SV720	Kawasaki V twin
No. of cylinders	1	1	2	2
Cooling system	Air	Air	Air	Air
Fuel capacity, gal. (L)	3 (11.4)	3 (11.4)	3 (11.4)	5 (18.9)
Full pressure lubrication	Standard	Standard	Standard	Standard
Starter key w/safety interlock	Standard	Standard	Standard	Standard
Air cleaner, dual element	Standard	Standard	Standard	Standard
Drive System				
Type	Dual Hydrostatic: Transaxle with integral pump and motor; One at each wheel			
Max speed, forward, mph (kph)	7.0 (11.3)	7.0 (11.3)	7.0 (11.3)	7.0 (11.3)
Max speed, reverse, mph (kph)	3.4 (5.5)	3.4 (5.5)	3.4 (5.5)	3.4 (5.5)
Implement clutch	Electric	Electric	Electric	Electric
Brakes				
Service Brake	Hydrostatic Dynamic Braking			
Parking Brake Lock	Automatic engagement with steering levers in neutral			Manual, LH lever
Electrical				
Voltage	12 volts	12 volts	12 volts	12 volts
Charging System (amps)	15	15	15	13
Battery, cca	195	195	195	260
Operator Station and Controls				
Steering	Dual padded lever hydrostatic with hydraulic dampening			
Seat Type	Contoured, high back, adjustable fore and aft			
Armrests	Optional	Optional	Standard	Standard
Cup Holder	Standard	Standard	Standard	Standard
Storage Bin	Standard	Standard	Standard	Standard
Front Casters	Double yoke	Double yoke	Double yoke	Double yoke
Wheels and Tires				
Front Casters	10 x 4 ribbed	10 x 4 smooth	10 x 4 smooth	10 x 4 ribbed
Rear	18 x 7.5-8, 2-ply	18 x 9.5-8, 2-ply	18 x 9.5-8, 2-ply	18 x 10.5-10, 4-ply
Dimensions, in. (cm)				
Length, overall				
with grass catcher	90.0 (228.6)	90.0 (228.6)	90.0 (228.6)	N/A
less grass catcher	73.1 (185.7)	73.1 (185.7)	73.1 (185.7)	77.5 (196.9)
Width, overall				
with deck deflector down	53.8 (136.7)	63.0 (160.0)	63.0 (160.0)	65 (165.1)
with deck deflector up	46.0 (116.8)	53.5 (135.9)	53.5 (135.9)	58 (147.3)
with grass catcher	52.8 (134.1)	56.8 (144.3)	56.8 (144.3)	N/A
Height, overall, to top of seat	37.2 (94.5)	40.2 (102.1)	40.2 (102.1)	41 (104.1)
Wheelbase	48.1 (122.2)	48.1 (122.2)	48.1 (122.2)	52.1 (132.3)
Turning Radius, inside rear wheel	Zero turn	Zero turn	Zero turn	Zero turn
Net weight, estimated, lb. (kg)	500 (226.8)	552 (250.4)	565 (256.3)	680 (309)
Mower Decks (optional mulching kits available)				
42 in. side discharge	Standard	—	—	—
50 in. side discharge	—	Standard	Standard	—
52 in. side discharge	—	—	—	Standard
Spindles	2	3	3	3
Anti-scalp gauge wheels	Standard	Standard	Standard	Standard
Attachments & Accessories				
2-bag grass catcher (8 cu. ft.)	Optional	Optional	Optional	N/A
56-inch front blade	N/A	N/A	N/A	Optional
Rear engine guard	Optional	Standard	Standard	N/A
Engine top cover	Optional	Optional	Optional	N/A
Foot assist height of cut kit	Optional	Optional	Standard	N/A
Headlights	N/A	N/A	N/A	Optional
Smooth-tread front tires	Optional	Standard	Standard	Optional

Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377



NEW HOLLAND

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2007 CNH America LLC
New Holland is a registered trademark of CNH America LLC.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

NH3160702 • 040720 • XXX • PRINTED IN U.S.A.